

# Thermal transfer printer - THERMOMARK PRIME - 5148888

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Thermal transfer printer for mobile or stationary use, with integrated "MARKING SYSTEM APP" marking software on board, 7" color touch display and replaceable battery pack. Can be linked to CLIP PROJECT, for printing plastic markers in UCT, US, and UM format.



## Key Commercial Data

Packing unit	1 STK
GTIN	
GTIN	4055626041834

## Technical data

### General

Interface	10/100 Mbps Ethernet
	USB 2.0
Weight	6.00 kg

### Dimensions

Length	292.00 mm
Height	122.00 mm
Width	224.00 mm

### Connection data

Minimum voltage	100 V AC
Max. voltage	240 V AC
Additional text	50 Hz ... 60 Hz

### Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

# Thermal transfer printer - THERMOMARK PRIME - 5148888

## Approvals

Approvals

---

Approvals


EAC

---

Ex Approvals

---

## Approval details

EAC		RU *- DE.A*30.B.02513
-----	---	--------------------------

---

Phoenix Contact 2017 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>